

## TLP-43-056-200

The TLP-43-056-200 telecentric lens was engineered to integrate Optotune's electrically tunable lenses directly into the optical path. This optimized design preserves telecentricity, minimizes magnification change, and ensures excellent optical performance. The TLP-43-056-200 is available with two different liquid lens models.

- EL-12-30-TC-VIS-16D: Faster and more economical
- EL-16-40-TC-VIS-5D: Higher repeatability and very good line of sight stability with pixel shift well below 1px

### Lens module specifications

	EL-12-30-TC-VIS-16D			EL-16-40-TC-VIS-5D			
Magnification	0.561	0.561	0.559	0.563	0.563	0.559	X
Working distance <sup>1</sup>	200	200	214	199	199	213	mm
HFOV	32.8	32.8	32.9	32.7	32.7	32.9	mm
VFOV	24.6	24.6	24.7	24.5	24.5	24.7	mm
Focal power	0	0	-1	0	0	-1	Dpt
Magnification change	0.032			0.050			%/mm
Focus sensitivity	14.00			14.00			mm/dpt
F/# (fixed)	8.8						
Maximum sensor format	4/3"						inch
Maximum image circle (Φ)	23						mm
Pixel size (recommended)	2.4						μm
Resolution test with USAF target	102						lp/mm
Optical distortion	<0.023						%
Telecentricity	<0.1						°
Wavelength range	400-700						nm
Mount	C-mount						
Filter thread	M59.5x0.5						
Dimension (Φ x L)	62 x 218						mm
Operating temperature	-20 to +65						°C
Storage temperature	-40 to +85						°C
Lifecycles (10-90% sinusoidal)	>1'000'000'000						cycles

### Focus tunable lens specifications

	EL-12-30-TC-VIS-16D	EL-16-40-TC-VIS-5D	
Focal power range (@25°C)	-6 to +10	-2 to +3	dpt
Settling time with / without signal conditioning	10 / 20	12.5 / 25	ms
Temperature sensor and EEPROM	Yes		
Control current (typical)	-250 to +250		mA
Max. control current	-300 to +300	-500 to 500	mA
Motor coil resistance @ 30°C	15	12	Ω
Absolute maximum voltage (coil)	6	10	V
Absolute maximum voltage (temp. sensor)	4.3	4.3	V

<sup>1</sup> Recommended working distance range based on performance tests. Note that both liquid lenses provide a larger focal power range and with that significantly larger working distance ranges are possible, but resolution might drop beyond the recommended range.

## Embedded controller specifications<sup>2</sup>

Supply voltage range	5 and 9-24 (tolerance ± 5%)	VDC
Maximum power consumption (5V / 9-24V)	1.5 / 2.5	W
Analog voltage inputs level	0-10	V
Digital signal logic level	3.3	V

## Overview of available standard products

Standard Product	Liquid lens integrated	Connector	Controller	Typical interface
TLP-43-056-200-12EC1	EL-12-30-TC-VIS-16D	Hirose (female)	ECC-1C (embedded)	I2C, UART, Analog 0-10 V UART to USB cable available.
TLP-43-056-200-16	EL-16-40-TC-VIS-5D	Hirose (male)	ICC-1C, ICC-4C-500 (not included)	USB, Ethernet, Analog 0-10 V

## Control

The focus tunable lens is controlled with electrical current and must be operated by a suitable lens controller. The following controllers are fully compatible:

- Optotune embedded controller ECC-1C (included in -EC1 configuration, compatible with selected cameras)
- Optotune industrial controller ICC-1C
- Optotune industrial controller ICC-4C-500



Further information about Optotune's controllers is available at [www.optotune.com/controllers](http://www.optotune.com/controllers).

## Electrical layout


Hirose connector (HR10G-7R-6PB)	Function	Sensor pins	
Pin 1	Control current +	-	
Pin 2	Control current -	-	
Pin 3	Ground	1-4	
Pin 4	Vcc (3.0-3.7V)	8	
Pin 5	I <sup>2</sup> C SCL	6	
Pin 6	I <sup>2</sup> C SDA	5	

Table 1: Pinout of the TLP-43-056-200 with male Hirose connector (for external controller).

Hirose connector (HR10G-7R-6SB)	Function	Value	
Pin 1	GPIO Trigger	-	
Pin 2	Analog In	0-10V	
Pin 3	UART Tx / I <sup>2</sup> C SCL	TTL	
Pin 4	UART Rx / I <sup>2</sup> C SDA	TTL	
Pin 5	GND	-	
Pin 6	Vcc	5-24V	

Table 2: Pinout of the TLP-43-056-200 with female Hirose connector ("EC1" version with ECC-1C integrated).

<sup>2</sup> Applies to the -EC1 version of the ELM. For more information, please refer to the [ECC-1C datasheet](#).

